

SUNBEAM (GB)									
Rapier Série I, II et III	-	6,4/1°05'	0°45'±15'	3°40'±15'	5°15'±15'				*
Alpine I et II Série V	-	3,2/0°32'	0°45'±15'	4°40'±30'	5°15'±15'				*
Tiger (V8)	-	3,2/0°32'	0°45'±15'	4°40'±30'	5°15'±15'				*
Rapier IV et V	-	4,8/0°48'	0°30'±15'	0°30'±15'	5°15'±15'				*
Rapier H 120	-	3±1,5/ 0°30'±15'	0°±45'	0°15'±30'	11°30'±45'				
Imp Husky Chamois	-	3±1,5/ 0°30'±15'	2°15'±1°30'	9°±1°	8°45'±1°30'				*
Stiletto + Sport	-	3±1,5/ 0°30'±15'	2°15'±1°30'	9°±1°	8°45'±1°30'				*
1250	-	2±1/ 0°20'±10'	1°±45'	1°±30'	11°30'±45'				
1300 / 1300TC	-	1-3/ 0°10' - 0°30'	1°±45'	1°±30'	11°30'±45'				
1500	-	2±1/ 0°20'±10'	1°±45'	1°±30'	11°30'±45'				
1600 tous types	-	1-3/ 0°10' - 0°30'	1°±45'	1°±30'	11°30'±45'				
Hunter	-	3±1,5/ 0°30'±15'	0°±45'	0°15'±30'	11°30'±45'				
Scepter - Alpine GT	-	3±1,5/ 0°30'±15'	0°±45'	0°15'±30'	11°30'±45'				
Alpine Fastback	-	3±1,5/ 0°30'±15'	0°±45'	0°15'±30'	11°30'±45'				*

Observations :

* - Réglages effectués en charge.